
British Laser Diode QSFP-DD



Overview

The DWDM-QSFP-DD-120KM is a C-band 75G/100 GHz grid coherent opticalmodule thatcombines coherent DSP ASIC functionality with best in class ultra-narrow line-width tunable lasers, high speed modulators and high responsively coherent receivers to deliver high performance at 400G. The DWDM-QSFP-DD-120KM is a C-band 75G/100 GHz grid coherent opticalmodule thatcombines coherent DSP ASIC functionality with best in class ultra-narrow line-width tunable lasers, high speed modulators and high responsively coherent receivers to deliver high performance at 400G. QSFP-DD MSA family of modules and cages remain fully backward 22 compatible with the classic QSFP+ formfactor. This document provides a common specification for systems 25 24 23 manufacturers, system integrators, and suppliers of modules. 34 purpose, or any other warranty otherwise arising out of. Abstract: This specification defines: the electrical and optical connectors, electrical signals and power supplies, mechanical and thermal requirements of the pluggable QSFP Double Density (QSFP-DD/QSFP-DD800) and the QSFP112 module in the classic 4-lanes QSFP form factor, connector and cage. The Cisco ® family of QSFP-DD modules provide the industry's highest bandwidth density while leveraging the backward compatibility to lower-speed QSFP pluggable modules and cables. The Cisco 400GBASE Quad Small Form-Factor Pluggable Double Density (QSFP-DD) portfolio offers customers a wide variety. QSFP-DD, standing for Quad Small Form-factor Pluggable Dual Density, is an optical transceiver dedicated to 200G and/or 400G applications, compatible with QSFP-DD ports of any brand of equipment. L2K offers a complete range of QSFP-DD transceivers along with unique services such as testing, coding. Optical modules are not “just optics”: they are tightly-coupled electrical recovery/equalization, optics bias/monitoring, and power/thermal control in a pluggable package. 32 purpose, or any other warranty otherwise arising out of any proposal.

© 2026 ALFA PRO COMMUNICATION SYSTEMS (Pty) Ltd - All rights reserved

Article Content

Specification – QSFP-DD

July 11, 2019 – QSFP-DD Hardware Specification for QSFP DOUBLE DENSITY 8X PLUGGABLE TRANSCEIVER – Rev 5.0 May 8, 2019 – Common Management Interface

QSFP-DD Hardware

20 mechanical and thermal requirements of the pluggable QSFP Double Density (QSFP-DD/QSFP-DD800/QSFP- 21 DD1600) connector and cage system. QSFP-DD MSA family of modules and

QSFP-DD Hardware

This specification defines: the electrical and optical connectors, electrical signals and power supplies, 19 mechanical and thermal requirements of the pluggable QSFP Double Density (QSFP-DD/QSFP

L2K Quad Small Form-factor Pluggable Dual Density Transceivers

QSFP-DD, standing for Quad Small Form-factor Pluggable Dual Density, is an optical transceiver dedicated to 200G and/or 400G applications, compatible with QSFP-DD ports of any brand of

QSFP-DD Hardware

Chapter 9 describes an improved QSFP+ form factor called QSFP112 39 with improved signal integrity for 100 Gb/s per lane operation and with an aggregate bandwidth of 400 Gb/s.

400ZR Coherent QSFP-DD Optical Transceiver Module

The module is QSFP-DD type2 size (18.4 mm x 93.4 mm x 8.5 mm) and hot pluggable by a 76-pin connector. The maximum power consumption is 16.5 W and power supply voltage is +3.3V.

InnoLight''s QSFP-DD Optical Transceiver

This report is an exhaustive analysis of the InnoLight 400G QSFP-DD optical transceiver, including a full analysis of the laser die, photodiode die, the TIA circuit, GaAs laser driver circuit, the PAM4 DSP

Global Leader in Materials, Networking, and Lasers

Learn how Coherent empowers innovations and breakthrough technologies for the industrial, communications, electronics, and instrumentation markets.

Specification – QSFP-DD

© 2026 ALFA PRO COMMUNICATION SYSTEMS (Pty) Ltd - All rights reserved

August 7, 2020 – QSFP-DD Hardware Specification for QSFP DOUBLE DENSITY 8X PLUGGABLE TRANSCEIVER – Rev 5.1 July 11, 2019 – QSFP-DD Hardware Specification for QSFP

Cisco QSFP-DD800 Transceiver Modules Data Sheet

For more information and references on QSFP-DD cable guides, please click on the following link: Cisco Transceiver Modules - Brochures - Cisco Cisco QSFP-DD800 transceiver

COLORZ® II 400ZR+ QSFP-DD Product Brief

The COLORZ II 400ZR+ QSFP-DD utilizes 7 nm coherent DSP technology, including its low power SD-FEC as well as innovative silicon photonics, driver, and TIA technology to provide coherent

QSFP-DD Fibre Optic Transceiver Technology

QSFP-DD Fibre Optic Transceiver Technology Overview QSFP-DD The QSFP-DD (Quad Small Form-factor Pluggable – Double Density) form-factor is used for

800G Transceiver Overview: QSFP-DD and OSFP Packages

This article provides an overview of 800G optical transceivers, focusing on the QSFP-DD and OSFP packages. Explore the features, differences of these high-speed transceiver form factors

400G OSFP/QSFP-DD/QSFP112 Module Introduction and Selection

This article explores the technical characteristics, product lineup, and use cases of 400G OSFP/QSFP-DD/QSFP112 modules to choose the most suitable 400G solution for your data centers.

QSFP DOUBLE DENSITY 8X PLUGGABLE TRANSCEIVER

Abstract: This specification defines: the electrical and optical connectors, electrical signals and power supplies, mechanical and thermal requirements of the pluggable QSFP Double Density (QSFP-DD)

QSFP-DD Optical Transceivers for High-Speed Connections

QSFP-DD ports incorporate a riding heatsink that can be sized independently of the optical module, added on top of the module, or placed between modules. This flexibility enables switch and routing

Unlocking the Future of Connectivity: Understanding QSFP-DD ...

Discover the future of connectivity with QSFP-DD transceivers. Learn how this compact, high-density interface enhances 200G/400G interconnect solutions.

© 2026 ALFA PRO COMMUNICATION SYSTEMS (Pty) Ltd - All rights reserved

QSFP-DD Connector System

QSFP-DD Interconnect System''s 8-lane electrical interface transmits 28G NRZ, 56G PAM-4 and 112G PAM-4, up to 200, 400 or 800 Gbps aggregate. Backwards compatible with QSFP.

Contact Us

Continue your research online:

Website: https://alfa-pro.co.za
Technical inquiry: https://alfa-pro.co.za/contact.html

This document is for preliminary research. Verify specifications against current standards, product documentation and project requirements.

© 2026 ALFA PRO COMMUNICATION SYSTEMS (Pty) Ltd - All rights reserved