

# Determining the Spacing Between Cable Tray Hangers



## Overview

Discover the essential cable tray spacing requirements for safe and efficient installation. Learn key standards, horizontal and vertical spacing, and more.

## Key Takeaways

Cable tray hangers should be spaced to support the tray and cables safely, typically ranging from 1.5 to 3 meters depending on tray type, cable weight, and installation conditions.

## General Guidelines

The spacing between cable tray hangers is critical to prevent sagging, maintain structural integrity, and ensure safe cable support. For standard installations:  
Horizontal runs: Hangers are generally spaced every 1.5 to 3 meters for ladder or ventilated trays, depending on the tray material, width, and the total weight of the cables supported.

Vertical runs: For vertical risers, hangers or supports should be installed at shorter intervals, often 1 to 1.5 meters, to prevent stress on the cables and tray. Heavy or densely loaded trays: If the tray carries heavy power cables or large bundles, the spacing should be reduced to maintain stability and prevent excessive deflection.

## Factors Affecting Hanger Spacing

**Tray Type and Material:** Steel trays can span longer distances than aluminum or plastic trays due to higher stiffness. **Cable Weight and Size:** Heavier cables require closer hanger spacing to avoid sagging and mechanical strain. **Environmental Conditions:** Outdoor installations or areas with vibration, wind, or seismic activity may require closer hanger spacing.

**Deflection Limits:** For flexible systems, calculations are often performed to limit tray deflection to 2% of the span to prevent cable displacement.

## Practical Recommendations

**Rung spacing:** For ladder-type trays, rungs are typically spaced 150–230 mm apart to support cables adequately. **Parallel trays:** Maintain at least 0.6 meters between trays for maintenance and airflow.

**Power vs. signal trays:** Keep at least 0.5 meters apart to reduce electromagnetic interference, or 0.3 meters if shielded.

**Hanger rod diameter:** Minimum 8 mm for stability.

## Summary

Proper hanger spacing ensures tray stability, prevents cable damage, allows heat dissipation, and facilitates maintenance. Always consider tray type, cable load, environmental factors, and applicable standards (e.g., BS EN 61537, BS 6946) when determining hanger intervals. For precise installations, especially with heavy or flexible cables, engineering calculations should be performed to confirm spacing and deflection limits.

## Article Content

### Cable Tray Spacing Standards for Installation and Safety

Discover the essential cable tray spacing requirements for safe and efficient installation. Learn key standards, horizontal and vertical spacing, and more.

### Cable Tray Support Spacing: Key Guidelines Explained

Explore the essential cable tray support spacing requirements for safe and efficient installations. Learn NEC guidelines for perforated, ladder, and wire

### Product Advice: Bracket Spacing Considerations

Traditionally, it has been recommended to install brackets approximately every 1 to 1.5 meters along the length of the cable tray. However, this guideline isn't set in stone. There are factors to consider when

## Cable Support Distances

For flexible systems, where the cable is not directly fixed to the support system, for example a J hanger installation, calculations need to be undertaken to determine the required distance between the cable

## Best Practice Guide to Cable Ladder and Cable Tray Systems

The radius for cable ladder and cable tray fittings is usually determined by the bending radius and stiffness of the cables installed on the cable ladder or cable tray.

## Ultimate Guide to Cable Tray Hanging Systems: Choice and Installation

Get to know how to select and install cable tray hanging systems. This guideline addresses the load capacity, spacing and material finishes to maintain the project safety and stability

## Cable Tray Technical Guide A practical guide to product selection and ...

Cable tray length is selected based on the load to be supported, the distance between the supports (also referred to as the span), and handling and installation constraints.

## Guide to cable support systems

The mesh cable trays are suitable for the installation of power cables and cables in various areas of application. The grid spacings mean that cables can be inserted and run out in various directions.

## Best Practice Guide to Cable Ladder and Cable Tray Systems

This guide covers cable ladder systems, cable tray systems, channel support systems and associated supports intended for the support and accommodation of cables and possibly other electrical

## Product Advice: Bracket Spacing Considerations

There are factors to consider when determining the appropriate bracket spacing for your installation. Optimizing Bracket Spacing: Weight Distribution: The weight of the cables and the tray itself is a

## Cable Cleats Catalog Cooper B Line | PDF

Cable Cleat Selection and Specification Step 5: Determine Cleat Spacing for Installation Your cable diameter is equal to the spacing between conductor

## CABLE LAddEr TrAY

Cable Management Systems permit much greater spacing between support hangers than most other systems, providing savings in support costs and installation labor.

## CABLE TRAY SYSTEMS GUIDE

Steel Ladder System Hubbell's NEXTFRAME® Ladder Tray is the effective and widely used cable runway that supports and delivers bundles of cable between cabinets, racks, and closets, along

Criteria for Sizing, Designing, Installing and Supporting of Cable-Tray ...

9.7 Cable-Tray Support: Cable trays shall be fastened to support steel by using guides that allow for longitudinal movement. 9.7.1 Whenever possible, supports and hangers shall be designed to permit

NEMA BI 50016-2024

408 trough or ventilated cable tray: A fabricated structure consisting of integral or separate longitudinal rails 409 and a bottom having openings sufficient for the passage of air and utilizing 75% or less of

## TECHNICAL GUIDE

This standard defines configurations for the mechanical tests to be performed on cable trays, brackets, hangers and other accessories. It also specifies the requirements and methods for the electrical

Cable Tray Width Selection for Installations with 600 Volt Single

Space between cables must be equal to one cable diameter --  $11 \times 1.07 \text{ inches} = 11.77 \text{ inches}$ . Total cable tray width required is  $12.84 \text{ inches} + 11.77 \text{ inches} = 24.61 \text{ inches}$ .

Guide to cable support systems

The systems allow large sup-port spacings of wide span systems or the multilayer arrangement of cable trays and cable ladder systems. The systems comprise I hanging supports, support brackets, head

Related Video Reference

This video was associated with the source search result. Verify technical details against current product documentation and project requirements.

## Contact Us

Continue your research online:

Website: <https://alfa-pro.co.za>

Technical inquiry: <https://alfa-pro.co.za/contact.html>

This document is for preliminary research. Verify specifications against current standards, product documentation and project requirements.

