Internal compartment of the secondary beam splitter box



Overview

A beam splitter or beamsplitter is an optical device that splits a beam of light into a transmitted and a reflected beam. It is a crucial part of many optical experimental and measurement systems, such as interferometers, also finding widespread application in fibre optic telecommunications.

Key Takeaways

The internal compartment of a secondary beam splitter box typically contains one or more beam splitter elements, such as cube or plate prisms, mounted to direct and divide light into transmitted and reflected paths.Core Components

© 2026 ALFA PRO COMMUNICATION SYSTEMS (Pty) Ltd - All rights reserved

Beam Splitter Element: The heart of the compartment is the beam splitter itself, which can be a cube prism or a plate. Cube beam splitters are made from two triangular prisms glued together with a partially reflective coating on the hypotenuse surface, allowing a portion of the light to be transmitted and the remainder reflected at a precise ratio . Plate beam splitters are thin glass plates with a reflective coating on one surface and an anti-reflection coating on the opposite side to minimize unwanted reflections . Mounting and Alignment: Inside the box, the beam splitter is securely mounted to maintain precise angles, typically 45° relative to the incoming beam. This ensures accurate splitting and minimizes beam deviation or misalignment . Some boxes may include adjustable mounts for fine-tuning the optical path. Coatings and Optical Layers: The internal surfaces may feature metallic, dielectric, or dichroic coatings to control the reflection/transmission ratio and polarization properties. Dielectric coatings are often fine-tuned for specific wavelengths, while metallic coatings like aluminum provide broadband reflection . Anti-reflection coatings on the exit surfaces reduce ghost images and maximize light throughput. Light Path Management: The compartment may include baffles or internal walls to prevent stray light from scattering, ensuring that only the intended transmitted and reflected beams exit the box. In multi-beam systems, additional mirrors or prisms may be present to redirect beams to secondary outputs or cameras . Optional Polarization Control: In polarizing beam splitter boxes, birefringent materials or Wollaston prisms may be included to separate orthogonal polarization states, directing them along different paths within the compartment .

Functionality

The internal compartment is designed to split, combine, or redirect light beams with minimal loss and precise control over intensity ratios. It ensures that the output beams maintain the desired polarization, wavelength characteristics, and spatial alignment for downstream optical systems, such as interferometers, microscopy setups, or multi-camera imaging systems . In summary, the secondary beam splitter box houses the optical elements, coatings, mounts, and light management structures necessary to accurately divide or combine light beams while preserving optical quality and alignment.

© 2026 ALFA PRO COMMUNICATION SYSTEMS (Pty) Ltd - All rights reserved

Article Content

Beam splitter

OverviewDesignsPhase shiftClassical lossless beam splitterUse in experimentsQuantum mechanical descriptionReflection beam splitters

A beam splitter or beamsplitter is an optical device that splits a beam of light into a transmitted and a reflected beam. It is a crucial part of many optical experimental and measurement systems, such as interferometers, also finding widespread application in fibre optic telecommunications.

Contact Us

Continue your research online:

Website: https://alfa-pro.co.za
Technical inquiry: https://alfa-pro.co.za/contact.html

This document is for preliminary research. Verify specifications against current standards, product documentation and project requirements.

© 2026 ALFA PRO COMMUNICATION SYSTEMS (Pty) Ltd - All rights reserved