# Laser diode PWM dimming frequency



## Overview

Laser Diode PWM Control and Its Consequences on Optical This article deals with frequency PWM (pulse-width modulation) control methodology and experiments.

## Key Takeaways

For laser diodes, PWM dimming frequencies typically range from 10 kHz to 50 kHz to ensure safe operation, effective brightness control, and minimal optical distortion.

### Recommended Frequency Range

Laser diodes are current-driven devices, and their optical output can be modulated using PWM without changing the peak current during the “on” portion of the cycle. Studies on InGaN edge-emitting lasers show that PWM frequencies between 10 kHz and 50 kHz allow effective control of lasing thresholds while minimizing distortion in power and spectral characteristics. Lower frequencies may cause visible flicker, stroboscopic effects, or artifacts in imaging applications.

### Practical Considerations

Duty Cycle Control: The perceived brightness is proportional to the PWM duty cycle. For example, a 10% duty cycle means the laser is on for 10% of the cycle and off for 90%, reducing average optical output without changing peak current. Driver Requirements: Laser diodes should never be driven directly by microcontroller pins unless part of a low-power module.

High-power diodes require a constant-current driver capable of accepting PWM or TTL modulation. Avoiding Artifacts: Low PWM frequencies (below ~2 kHz) can produce flicker, banding, or stroboscopic effects, especially in cameras or fast-moving applications. Frequencies above 10 kHz are generally sufficient to avoid these issues.

© 2026 ALFA PRO COMMUNICATION SYSTEMS (Pty) Ltd - All rights reserved

Grayscale and Resolution: For applications like laser engraving, the PWM frequency may interact with movement speed and DPI settings. A frequency around 20 kHz is commonly used for diode modules to balance smooth grayscale control and optical stability.

### Summary

Safe and effective PWM range: 10–50 kHz for most laser diodes. Duty cycle: Adjusts perceived brightness without exceeding peak current. Driver: Use a constant-current driver with PWM input.

Avoid low frequencies: Prevent flicker, stroboscopic effects, and imaging artifacts. Application-specific tuning: For engraving or scanning, 20 kHz is a practical starting point, adjustable based on speed and resolution. By following these guidelines, PWM dimming can safely control laser diode brightness while maintaining optical performance and diode longevity.

## Article Content

Laser Diode PWM Control and Its Consequences on Optical

This article deals with frequency PWM (pulse-width modulation) control methodology and experiments related to a deep characterization of InGaN (Indium gallium nitride) EELs (Edge Emitting Lasers) and

(PDF) Laser Diode PWM Control and Its Consequences on Optical ...

The PWM signal, then, has generated the voltage for a laser diode of wavelength 650 nm. The frequency can be tuned approaching 0-5 MHz with the simplicity of the pulse width adjustment.

(PDF) Laser Diode PWM Control and Its Consequences on Optical ...

Threshold currents vary from 16-53 mA, with max output power reaching up to 155 mW. PWM frequencies between 10-50 kHz enable effective control of lasing thresholds with minimal distortion.

PWM frequency for a diode

The specs of my Odicforce laser diode mention a PWM frequency of 20KHz. I have set the PWM frequency on my controllerboard at that same speed. It looks tro be working, but have

LED Brightness Adjustment: High-frequency PWM Dimming

In short, to use PWM dimming and avoid its drawbacks, you should set the PWM dimming frequency higher than 2kHz. To achieve high-frequency dimming, most LED drivers have a PWM dimming

*© 2026 ALFA PRO COMMUNICATION SYSTEMS (Pty) Ltd - All rights reserved*

PWM Laser Driver Circuit Guide | PDF | Electronic Circuits

This document describes how to build a pulse width modulation (PWM) and frequency controller for lasers and diodes. It uses a 555 timer integrated circuit to independently control the frequency and

Arduino LASER Brightness Pulse Width Modulation PWM

PWM can make a laser appear dimmer by rapidly switching it on and off, but it is not a substitute for a correct current limit. Set the laser driver current to a safe value for the diode first, then

Experimental investigation of PWM laser standoff distance control for ...

The diode laser used here has the maximum frequency of 20 KHz and therefore, the ranges of 16 KHz, 18 KHz and 20 KHz have been considered in order to vary and obtain the results

SSZTAY6 Technical article | TI

LED Brightness Adjustment: High-frequency PWM Dimming Issac Hsu In one of my previous blog posts, I introduced different dimming methods for light-emitting

PWM Laser Driver Circuit Guide | PDF

PWM and Frequency Controller for Lasers and Diode - Free download as PDF File (.pdf), Text File (.txt) or read online for free. This document describes how to build a pulse width modulation (PWM) and

Laser diode PWM control and its consequences on optical

Laser diode (LD) PWM driving can be also advantageous for LD lighting applications. In such a case PWM driving enables speckle-free dimming as the PWM is more suitable to suppress speckle

PWM Switching of 0-200mA Laser diode driver

A laser diode is effectively an LED, so you might want to consider an LED driver. The most common way to accomplish 0-100% dimming is to choose a voltage that will be 100% and PWM it.

analogue laser dimming using pwm signal. | All About Circuits

I assume that you are using a single laser to draw images on a wall. PWM is the usual method to control the intensity. You don''t need to filter the signal. Just make sure that the PWM

LED Brightness Adjustment: High-frequency PWM Dimming

*© 2026 ALFA PRO COMMUNICATION SYSTEMS (Pty) Ltd - All rights reserved*

LED Brightness Adjustment: High-frequency PWM Dimming Issac Hsu In one of my previous blog posts, I introduced different dimming methods for light-emitting diode (LED) drivers: analog and pulse-width

Pulse Width Modulation

Pulse Width Modulation (PWM) refers to controlling the optical output of a laser via manipulation of the source that drives the gain medium. For our RF-excited sealed CO2 lasers, this is accomplished by

MG3 PWM configuration instructions

MG3 PWM configuration instructions Overview The Pulse Width Modulation signal (PWM) can be configured in terms of polarity and frequency and connects to the PWM input on laser drivers, which

Dimming in Switched-mode LED Drivers

One of the key concerns in light-emitting diode (LED) driver designs is the dimming performance. Most designers use one of two methods: analog dimming or digital pulse-width modulation (PWM)

How to dim one of these cheap 5mW laser modules?

I used to have an old 3x LR44 lithium cell laser pointer for presentations. With the batteries slowly dying, the outputted beam also went dimmer. Recently I bought one of these cheap

Related Video Reference

This video was associated with the source search result. Verify technical details against current product documentation and project requirements.

*© 2026 ALFA PRO COMMUNICATION SYSTEMS (Pty) Ltd - All rights reserved*

## Contact Us

Continue your research online:

Website: https://alfa-pro.co.za
Technical inquiry: https://alfa-pro.co.za/contact.html

This document is for preliminary research. Verify specifications against current standards, product documentation and project requirements.

*© 2026 ALFA PRO COMMUNICATION SYSTEMS (Pty) Ltd - All rights reserved*