Measuring the performance of an optical receiver

Overview

Since the OSNR measurement does not involve a transmitter nor a receiver, it has been broadly adapted as a basic parameter to measure optical signal transmission performance.

Key Takeaways

The performance of an optical receiver is primarily measured by its sensitivity, bit error rate (BER), and tolerance to noise and inter-symbol interference (ISI).

Key Performance Metrics

Receiver Sensitivity: This is the minimum average optical power required at the receiver input to achieve a target BER. Higher sensitivity allows the receiver to operate effectively with lower input power, extending communication distance or improving tolerance to misalignment and atmospheric disturbances in free-space optical systems. Sensitivity is often expressed in terms of photons per bit, considering the photon energy at the operating wavelength and the system bit rate.

Bit Error Rate (BER): BER is the ratio of incorrectly detected bits to the total number of received bits. It is the most critical measure of transmission quality. Systems may use forward error correction (FEC) to reduce the effective BER, with typical FEC codes requiring input BERs of 10-2 to 10-3 to achieve output BERs better than 10^-15.

Q-

© 2026 ALFA PRO COMMUNICATION SYSTEMS (Pty) Ltd - All rights reserved

Factor: The Q-factor is a logarithmic representation of BER, providing a convenient way to express receiver performance in decibels. It helps in comparing different receiver designs and understanding trade-offs between sensitivity, noise, and signal quality.

Factors Affecting Performance

Noise Sources: Random noise, including thermal noise, shot noise, and relative intensity noise (RIN) from the transmitter, can degrade receiver sensitivity. Accurate performance evaluation requires analyzing these noise contributions.

Inter-

Symbol Interference (ISI): ISI occurs when pulses overlap due to limited bandwidth or dispersion, causing errors in bit detection.

Evaluating IS

I impact is essential for high-speed optical systems. Modulation Format: The choice of modulation affects receiver design. Direct-detection receivers are sensitive to intensity but not phase or polarization, whereas coherent receivers can detect any modulation format, allowing more flexibility.

Receiver Hardware: Photodetector type (e.g., PIN diode, avalanche photodiode), amplifier design, and demodulation circuitry influence performance. Limiting or automatic-gain-control amplifiers help maintain consistent signal levels for accurate bit detection.

Measurement Methods

Optical Power Sweep: Measure BER while varying input optical power to determine the minimum power achieving the target BER. Noise Analysis: Introduce controlled noise sources to quantify sensitivity degradation.

Timing and IS

I Tests: Use high-speed pulse sequences to evaluate the receiver's ability to resolve closely spaced bits.

FE

C Evaluation: Measure raw BER and decoded BER after FEC to assess practical system performance. By combining these metrics and tests, engineers can comprehensively evaluate an optical receiver's performance, optimize design parameters, and ensure reliable operation under expected system conditions.

© 2026 ALFA PRO COMMUNICATION SYSTEMS (Pty) Ltd - All rights reserved

Article Content

HFAN-03.0.2: Optical Receiver Performance Evaluation

This application note provides an in-depth analysis of the complete receiver optical sensitivity and the potential power penalties related to the accumulation of random noise and inter-symbol interference

Receiver Performance

Since the OSNR measurement does not involve a transmitter nor a receiver, it has been broadly adapted as a basic parameter to measure optical signal transmission performance.

Optical Receiver Performance

The receiver performance is characterized by measuring the BER as a function of the average optical power received. The average optical power corresponding to a BER of 10-9 is a measure of receiver

Optical Receivers | part of Fiber-Optic Communication Systems

The bandwidth of a photodetector is determined by the speed with which it responds to variations in the incident optical power. The chapter focuses on reverse-biased p–n junctions that are used for

HFAN-03.0.0: Accurately Estimating Optical Receiver Sensitivity

More often than not, designers will use a combination of simple estimation and "rules of thumb" to predict performance and select components. This discussion presents a reliable method for

Field Optical Receiver Guide: Specs, Installation, and Troubleshooting

Key Performance Specifications to Evaluate When comparing field optical receivers for a specific deployment, several specifications matter far more than a general sensitivity number on a datasheet

Mastering Receiver Sensitivity in Optical Communications

In essence, it measures how well a receiver can detect weak optical signals. A higher receiver sensitivity indicates better performance, as it can detect signals with lower power, enabling

Receiver Performance Analysis

In our concluding chapter we will combine our photodetector and receiver-noise modeling techniques with front-end and demodulator designs to construct complete receiver structures. Our goal is to

© 2026 ALFA PRO COMMUNICATION SYSTEMS (Pty) Ltd - All rights reserved

Mastering Receiver Sensitivity in Optical Communications

Discover the importance of receiver sensitivity in optical communications and learn how to optimize it for better signal quality and reliability.

How to Measure the Performance Indicators of Optical Modules?

The performance indicators for measuring optical modules are also divided into two categories: Transmitter End and Receiver End. Measuring the performance indicators of optical

Optical Receiver Performance Evaluation

This application note is all about optical receiver sensitivity which includes the possible effects on power output due to accumulation of random noise and intersymbol interference (ISI) in

Optical Receiver

Optical receiver characterization and calibration are important for both optical communication and instrumentation, which directly affect optical system performance and measurement accuracy. In this

Optical Receiver Configuration and Performance

This document provides an overview of optical receiver operation for digital signal transmission. It discusses the fundamental components and processes in a digital optical receiver including digital

Optical receiver performance evaluation

An essential parameter in determining the system power budget in an optical transmission system is optical receiver sensitivity, defined as the minimum average optical power for

Receiver Sensitivity

Receiver sensitivity and power margin have been widely used to specify the performance of optical receivers and optical transmission systems. In a traditional optical system without inline optical

WORK Microwave. Innovative RF electronics and digital

Optical Ground Station Virtualised DIFI Solutions Defence Electronics Sensors & Measurement The products of SatCom, Defence Electronics and Sensors &

HFAN-03.0.0: Accurately Estimating Optical Receiver Sensitivity

© 2026 ALFA PRO COMMUNICATION SYSTEMS (Pty) Ltd - All rights reserved

The portion of the receiver that contributes the most noise is the optical-to-electrical conversion provided by the photodetector and the transimpedance amplifier (TIA). More often than not, designers will use

Reference Guide to Fiber Optic Testing

1.1 Optical Communications n optical fiber to a distant receiver. The electrical signal is converted into the optical domain at the transmitter and is converted back into the orig nal electrical signal at the

Related Video Reference

This video was associated with the source search result. Verify technical details against current product documentation and project requirements.

Contact Us

Continue your research online:

Website: https://alfa-pro.co.za
Technical inquiry: https://alfa-pro.co.za/contact.html

This document is for preliminary research. Verify specifications against current standards, product documentation and project requirements.

© 2026 ALFA PRO COMMUNICATION SYSTEMS (Pty) Ltd - All rights reserved