Technical Requirements for Automation of Tail Fiber Processing

Overview

Automation eliminates the variability associated with manual labor, ensuring that each layer is positioned with utmost accuracy.

Key Takeaways

Automating tail fiber processing requires precise material handling, controlled slitting, defect monitoring, and integration with downstream fiber placement or web systems.

Material Preparation and Slitting

Automated fiber placement (AFP) and tape laying rely on narrow, slit tapes or “tows” that must meet strict dimensional tolerances to ensure quality and throughput. Key requirements include: Blade selection and maintenance: Carbide blades with appropriate coatings improve durability and reduce buildup when processing tough fibers. Slit width and spacing control: Accurate measurement of tape width and edge spacing ensures consistent layer placement and prevents defects.

Rewinding parameters: Outer diameter of takeup cores, traverse length, and taper angles must be controlled to maintain uniform tension and prevent material deformation. Environmental control: Thermoplastics may require light heating or LDPE wrapping, while thermosets need moisture-resistant bags with desiccants to preserve material integrity.

© 2026 ALFA PRO COMMUNICATION SYSTEMS (Pty) Ltd - All rights reserved

Process Parameters and Equipment

Automation requires precise control of AFP or tail handling equipment: Heating and compaction: Prepreg tapes are heated using hot nitrogen or lasers and consolidated with compaction rollers to ensure adhesion and laminate quality. Layup speed and tension: Optimized speed, compaction force, and tension reduce defects such as out-of-plane wrinkles. Tail threading and web handling: Vacuum conveyor systems, air blow nozzles, and grooved rolls guide the tail accurately through the process, minimizing downtime and ensuring smooth operation.

Splice and defect tracking: Dual verification of material length and intentional defect spools improve accuracy and allow real-time monitoring.

Quality Assurance and Monitoring

Defect detection: Visual inspection, encoder-based length verification, and digital break recording help identify and prevent defects early. Process window validation: Each material and geometry combination requires trials to determine optimal heating, pressure, and hold times. Data integration: Web monitoring systems and digital feedback loops provide actionable insights for troubleshooting and continuous improvement.

Design and Integration Considerations

Tape width selection: Narrow tows (0. 125–0. 250 inch) are preferred for complex geometries, while wider tapes (0.

500 inch) improve throughput when feasible. Equipment customization: Fiber placement heads and tail threading systems should be tailored to project-specific bandwidth and geometry requirements. Automation benefits: Reduces human error, scrap, and floor space while improving repeatability, structural performance, and overall productivity.

Summary

Efficient automation of tail fiber processing combines precision slitting, controlled material handling, optimized AFP parameters, and robust quality assurance. Environmental controls, real-time monitoring, and equipment customization are essential to maintain material integrity, minimize defects, and maximize throughput in high-performance composite or fiber-based manufacturing systems.

© 2026 ALFA PRO COMMUNICATION SYSTEMS (Pty) Ltd - All rights reserved

Article Content

A short review on recent advances in automated fiber placement and ...

Automation eliminates the variability associated with manual labor, ensuring that each layer is positioned with utmost accuracy. It is especially crucial for applications where high degrees of

QUALIFICATION METHOD FOR AUTOMATED FIBRE PLACEMENT

Abstract: Automated Fibre Placement (AFP) is an advanced process for the manufacturing of high-performance composite structures and is established in the aerospace industry.

Process and Design Considerations for Automated Fiber Placement

Automated Tape Laying and Automated Fiber Placement eliminate human error and improve accuracy and repeatability while maximizing structural strength-to-weight ratios in complex shapes. It reduces

Automated fiber placement: A review of history, current technologies ...

Automated fiber placement (AFP) is a composite manufacturing technique used to fabricate complex advanced air vehicle structures that are lightweight with superior qualities. The

Automated Fiber Placement

The accuracy and repeatability of the automated process ensures consistent quality and reduced material waste. At Broetje-Automation we are able to provide multiple production scenarios

Fiber Placement | Trelleborg''s Advanced Composites

Automated Fiber Placement (AFP) is traditionally used on complex surfaces and smaller structures. We utilize narrow, slit tapes, or “tows,” to make up a given total prepreg band width. In both thermoset

White paper: Total Tail Control

Combining our latest tail threading technology with digital break recording and web monitoring systems provides valuable information about the tail threading process. It offers a useful tool for

The Insane Engineering Behind Automated Fiber Placement

Whether you''re an industry professional, an engineering student, or simply curious about cutting-edge technology, this exploration of AFP will provide you with a comprehensive understanding of a

© 2026 ALFA PRO COMMUNICATION SYSTEMS (Pty) Ltd - All rights reserved

Automated fibre placement (AFP)

Utilizing advanced automation technology, AFP ensures tightly controlled processing conditions, allowing for the fabrication of high-quality laminates. Compared to conventional material deposition

White paper: Total Tail Control

Executive Summary When you have total tail control throughout the machine it clearly enhances production line efficiency. Valmet offers a full range of advanced tail threading solutions for all

Fiber Processing Solutions | JR Automation

Automated fiber processing refers to the use of advanced technologies such as robotics, sensors, and software to enhance the production of fiber, film, web or composites. JR Automation empowers fiber

Automated fiber placement: A review of history, current technologies ...

Carbon fiber materials became available for commercial use in 1966 stemming from research done by Watt et al. at the Royal Aircraft Establishment. Soon after its appearance, it

A short review on recent advances in automated fiber placement and ...

In this short review, recent developments in both automated fiber alignment technologies are presented and discussed, including the main advantages and materials used. Regarding the ATL

Continuous Improvement in Composite Manufacturing: A Review of ...

Continuous improvement and refinement on the application level of composites is essential for advancing the capabilities and reliability of various industries. Automated Fibre

Fiber and Textile Automation

Enhance your fiber and textile manufacturing processes with textile automation. We offer a range of solutions specifically for textile manufacturing.

Automated Composite Manufacturing

Automated composite manufacturing is defined as the use of machines, such as automated tape layup (ATL) or automated fiber placement (AFP), to enhance the efficiency, repeatability, and precision of

Automated Fiber Placement Process: Design Cycle ...

© 2026 ALFA PRO COMMUNICATION SYSTEMS (Pty) Ltd - All rights reserved

Automated fiber placement (AFP) is a process used to manufacture composite materials in which continuous fibers are placed onto a substrate using a specialized machine.

Fiber Machinery and Equipment

Both of these qualities negatively influence the production process and the resultant quality of the yarns made from it. One of the common ways to

Contact Us

Continue your research online:

Website: https://alfa-pro.co.za
Technical inquiry: https://alfa-pro.co.za/contact.html

This document is for preliminary research. Verify specifications against current standards, product documentation and project requirements.

© 2026 ALFA PRO COMMUNICATION SYSTEMS (Pty) Ltd - All rights reserved