Voltage between distribution boxes

Overview

Electricity is delivered at a frequency of either 50 or 60 Hz, depending on the region. It is delivered to domestic customers as. In some countries as in Europe a supply may be made available for larger properties. Seen with an, the domestic power supply in North America would look like a, oscillating between −170 volts and 170 volts, giving an effective voltage of 12.

Key Takeaways

The voltage between standard low-voltage distribution boxes is typically 230/400 V in a three-phase system or 120/240 V in single-phase residential systems, depending on regional standards.Overview of Distribution Box Voltage

Distribution boxes, also called distribution boards or DB boxes, receive power from a transformer and distribute it to multiple circuits safely. In low-voltage networks, the primary distribution voltage from substations is stepped down by transformers to a secondary voltage suitable for consumer use. In Europe, this is usually 230 V phase-to-neutral and 400 V phase-to-phase for three-phase systems, while in the US, residential single-phase systems typically use 120/240 V .

Voltage Between Adjacent Distribution Boxes

The voltage measured between two distribution boxes depends on whether they are on the same phase or different phases:

• Single-phase systems: Each box receives the same nominal voltage from the transformer (e.g., 120 V in the US). Voltage between two boxes on the same phase is nearly zero, while between phase and neutral it is the nominal voltage (120 V).

© 2026 ALFA PRO COMMUNICATION SYSTEMS (Pty) Ltd - All rights reserved

• Three-phase systems: Boxes connected to different phases will have a line-to-line voltage (e.g., 400 V in Europe). Boxes on the same phase will have a voltage close to zero between them, with minor differences due to voltage drop along the distribution line .
Factors Affecting Voltage
• Distance from the transformer: Longer cable runs can cause voltage drops, reducing the voltage slightly at downstream boxes.

• Load on the circuit: High simultaneous demand can lower voltage at distribution boxes.

• Network configuration: Radial or looped distribution networks influence voltage stability between boxes .
Practical Considerations
• Distribution boxes are designed to maintain voltage within ±10% of nominal to ensure safe operation of appliances and equipment.

• Proper sizing of conductors and transformers minimizes voltage drop between boxes.

• Smart DB boxes can monitor voltage in real time, helping detect deviations and improve energy management . In summary, the voltage between distribution boxes is generally the nominal secondary voltage of the network, with minor variations due to distance, load, and network design. For residential systems, this is typically 120/240 V in the US or 230/400 V in Europe, while industrial or commercial installations may use higher three-phase voltages.

Article Content

Electric power distribution

OverviewSecondary distributionHistoryGeneration and transmissionPrimary distributionModern distribution systemsSee alsoExternal links

Electricity is delivered at a frequency of either 50 or 60 Hz, depending on the region. It is delivered to domestic customers as single-phase electric power. In some countries as in Europe a three phase supply may be made available for larger properties. Seen with an oscilloscope, the domestic power supply in North America would look like a sine wave, oscillating between −170 volts and 170 volts, giving an effective voltage of 12

© 2026 ALFA PRO COMMUNICATION SYSTEMS (Pty) Ltd - All rights reserved

Contact Us

Continue your research online:

Website: https://alfa-pro.co.za
Technical inquiry: https://alfa-pro.co.za/contact.html

This document is for preliminary research. Verify specifications against current standards, product documentation and project requirements.

© 2026 ALFA PRO COMMUNICATION SYSTEMS (Pty) Ltd - All rights reserved